

P R O D U C T / S E R V I C E S H E E T 1 0

## **FOUNDATIONS**

ATC can provide a variety of foundations depending on the location and specifications of your storage projects. Listed below are a few applications:

### **GRADE BAND**

Standard grade bands are 8 in. high x 5 ft. long. They are manufactured using 12 gauge galvanized sheet metal and connected using standard bolted tank hardware. Other gauges, heights, and lengths are also available. Standard roofing paper is applied over gravel before the tank is set. Check grade band chart to match diameter of tanks to number of bands needed.

### **TANK PADS**

Tank pads are typically used when setting a tank upon a concrete slab or metal floor. These pads consist of ½ in. to 1 in. thick CCA treated boards cut to the diameter of the tank. Creosote available upon request.

### **FIBER BOARD**

This type of foundation is usually applied between a concrete slab and the storage tank. The padding is available in 4 ft. x 8 ft. or 5 ft. x 10 ft. sheets. The excess pad is trimmed to fit the diameter of the tank.

### **CONTAINMENT RINGS**

Containment rings are popular on offshore platform locations. These rings are designed to assure the customer additional protection in the event of any leaks or spills. Tank pads are furnished to act as an insulator to keep the moisture from settling between the bottom of the tank and its foundation.

**Call 1.800.256.1626 to speak with an ATC Storage Tank Expert  
for Assistance or Additional Information.**